





**Cut-A-Way - Mini-Mover** 



Morgan KNOWS that heavy use DEMANDS durability AND dependability! That's why we designed AND built the Mini-Mover to last. Starting with our front end radius corner design. – the Mini-Mover keeps your business moving!



At Morgan, out-of-sight is NOT out-of-mind. Rest assured our subframe -- means your cargo and crew will be riding on the strongest, and best sub-frame in the business.

## STANDARD FEATURES

SIDE PANELS - 3/8" FRP (white gelcoat finish) panels

SIDE FRAME - extruded aluminum perimeter

FRONT WALL - 3/8" frp (white gelcoat finish) panels

FRONT AC DOOR - access to drivers compartment

UNDERSTRUCTURE - 1/4" steel strap long rails, 1 9/16" roll formed steel crossmember on 20" centers

MOUNTING - low-mount body with flat top steel wheelboxes

REAR FRAME - galvanealed steel, painted white, includes recessed incandescent taillights

GRAB HANDLES - roadside and curbside rear

REAR DOOR - Whiting plastic coated overhead door

LINING SIDES - seamless white fiberglass lining

REAR FINISH - full-width easy access step bumper

FLOOR - 5/8" marine grade exterior plywood undercoat

ROOF - .032" aluminum roof sheet with roof bows on 28" centers

EXTERIOR LIGHTS - per FMVSS-108, with reflectors and recessed taillights in rear corner posts

INTERIOR DOME - dome light with switch and indicator in cab

MIRRORS - factory supplied mirrors



Frequent movement in and out of the cargo area is made easier and safer by Morgan's wheel box design and lowered-floor configuration. A lowered-floor means a lower step-up and less stress on delivery personnel. And the slip-resistant surface and strategically positioned grab handles also lend to greater safety.



Easy Access Step Bumper



A variety of cargo configurations and securement options are available to make it easy to secure cargo at almost any point...and maximize payload.



## **OPTIONS**

Morgan Cut-A-Way bodies are already the best in the industry. But you can further enhance their performance with a wide range of options; from bumpers and cargo restraint systems, to liftgates and much more.

Trust Morgan to exceed your highest expectations.

- translucent roof
- two panel full opening swing rear doors
- single 36" wide centered swing rear door with barlock
- rows of apitong slats
- inside door lock with exterior handle for swing doors
- access door in cab
- omit sliding access door on front bulkhead
- 6" bulkhead, setback
- steel underride protector
- surface mounted tie ring
- four rows of 3/4" x 2 3/4" apitong slats mounted on Z bars (first row at floor level to act as scuff plate)
- extra row of 3/4" x 2 3/4" apitong slats mounted on plastic spacers (spaced at approximately 1/3 and 2/3 between floor and ceiling)
- two rows of 3/4" x 2 3/4" apitong slats, mounted on plastic spacers (spaced at approximately 1/3 and 2/3 between floor and ceiling)
- variety of liftgate and bumper configurations

Options That Set the Standard



An option for a recessed bulkhead that provides more room in the cab and easier positioning of the seat.

## Specifications - Cut-A-Way Mini-Mover

HEIGHT/WIDTH DIMENSIONS									
MODEL		REAR DOOR OPENING							
	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE HEIGHT*	INSIDE HEIGHT	WIDTH	HEIGHT**			
PVFP 72	79 ½"	78 ¾"	84 %16"	72 7/16"	71 ½"	66 7%"			
PVFP 78	79 ½"	78 <u>*</u> 8"	90 %16"	78 7/16"	71 ½"	72 7/8"			

	BODY LENGTH		VOLUME - CUBIC CAPACITY (FT.)			
MODEL	BODY LENGTH		MODEL	BODY LENGTH		
MODEL	10'	12'	MODEL	10'	12'	
OUTSIDE	10'6 ½"	12' 6 ½"	PVFP 72	400	479	
INSIDE***	10' 1¾"	12' 1 ¾"	PVFP 78	433	519	

NOTES:

\* Outside height dimension from bottom of sidewall to top of roof crown.

\*\* Overhead rear doors protrude into top of door opening 1" to 11/2" when in the up position.


\*\*\* Deduct 6.0" for recessed bulkhead.



For More Information Contact Your Morgan Representative or Authorized Morgan Distributor



888-350-4203 🔳 www.morgancorp.com



Products as shown may include optional equipment that is not part of the standard Morgan truck body configuration. Some product images may differ from current configurations and may not be available as depicted at the time of your order. NOTE: All dimensions, weights, and measurements specified herein are subject to Morgan's manufacturing tolerances, may change without notice, and may vary depending on options selected. Please Contact Morgan Representative for available options, complete up-to-date specifications and for measurements for your particular truck body and chassis specifications. ©Morgan Corporation 10/2012